

PRODUCT INFORMATION



VALVOLINE™ ALL-FLEET PLUS SAE 40

Valvoline All-Fleet Plus 40 is formulated from highly refined lube base stocks and carefully selected additive package comprising antioxidant, detergent/ dispersant, anti wear and a special oil soot thickening control agent.

Valvoline All-Fleet Plus 40 is recommended for use in high speed naturally aspirated and turbo charged diesel engines of all makes in commercial road transport , Off highway construction equipment, fishing boats and in generator sets .

PERFORMANCE LEVEL

API CF

Typical properties:

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Typical Characteristics	
Kinematic Viscosity, cSt @ 40°C	139.60
Kinematic Viscosity, cSt @ 100°C	14.38
Viscosity Index	101
TBN, mg KOH/g	5.6
Pour Point, °C, Max.	-21
Flash Point, COC, °C	230

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales representative or through our website <https://sds.valvoline.com/>

This information only applies to products manufactured in the following location(s): Singapore

Effective date
AUG 2020

Author
AS